
Update to HSE Pipeline Risk Assessment


Dr. Peter J Harper

HSE HID CEMHD5

Failure Rates


- PIPIN is HSE's model for predicting failure frequencies of pipelines
- Uses fracture mechanics to predict third party activity (TPA) failure rates
- Operational data for mechanical, corrosion and ground movement/other failure rates
- Developed in the late 90s by WS Atkins
- Current version is PIPIN V3.0

PIPIN



Gouge

Dent and gouge



Aspects Considered

- Rewriting the model to improve model resilience (reproduce existing results)
- Reviewing the science
- Updating the model based on the review
- Operational data
- Strike rates and damage data
- Depth of cover
- Slabbing

Science Review



- Model externally reviewed
- A number of suggestions made, including some of the correlations used for the fracture mechanics
- Each suggestion has been considered in turn and 584 test cases have been run each time
- Industry, external consultants and experts at HSL have been involved
- One area has been rejected on further investigation
- The rest have been approved by HSE
- Overall effect is to increase failure rates

Science Review



- Updates incorporated are:
 - Removal of modelling uncertainties
 - Removing simplification to an equation for dent-gouges (made it the same as for gouges)
 - Correcting the rupture calculation (removing double-counting – requires calculation of critical crack length which involves solving a cubic for every iteration of the model)
 - Revising the micro-crack correlation (removing the dependence on the industry model and using full dataset)
- The rejected modification was to the Charpy energy – fracture toughness correlation

Operational Data

- Operational data is used to provide historical information on mechanical, corrosion and ground movement/other failure rates.
- Previous analysis based on data up to ~2000
- Some European wide data was used as not enough UK specific data
- More recent data (up to 2010) has been analysed
- Problems arise when no incidents have occurred. How do you derive a rate?

Strike rates and damage data

- The damage data refers to the Weibull distributions used to determine the length and depth of the dent or gouge and the force with which the pipe is struck
- Analysed updated UKOPA data and tested several distributions to see which provided the best fit to the data
- Lognormal has been used for dent-gouge length and impact force, Weibull for gouge length and depth, and dent-gouge depth
- Updated data reduces failure rates

Risk Assessment



- MISHAP01 code rewritten in Excel for ease of updating (now MISHAP12)
- Individual models not changed
- Distances now rounded to $\pm 5\text{m}$
- Links to PIPIN V3.0
- Now links to mapping tool
- Individual models will be reviewed over next 2 years

NGG1454A: 9,52mm w.t.

o Const Bdy

Meon View

Issues

© Crown copyright and database rights 2013, Ordnance Survey 100021025



JGG1454B: 9.52 mm w.t., Slabbing adjacent to dev

